# Quantium 410 Fuel Dispenser





The Quantium 410 is Tokheim's global 'H' style, multiproduct dispenser. The 'hanging hose' design is easy to access and use. Better quality and reliability ensures greater uptime – this means your customers can rely on your service station. Not only does the Q410 benefit from Tokheim's renowned Quality, it is packed with the innovative and robust components that add genuine benefit to your business.

"The quality and reliability of the dispenser design is based upon the real-life, real-time data gathered from more than 40,000 service stations we directly support with our local organisations."



### Our Dispenser Range



### Quantium 110

Entry-level, one or two hoses, single-product system. Allows you to dispense one grade of fuel up to high speeds.



### Quantium 210

Entry-level dispenser, but with more options and flexibility than the Q110. The Q210 can dispense up to two products and it comes in either a one or two hose model.



### Quantium 310

Flexibly designed to deliver a single, twin or quad fuel dispenser. The spring mast based hose retractor system makes it easy for customers to use.



### Quantium 410

Tokheim's global 'H' style, multiproduct dispenser with 'hanging hose' design and a complete range of payment and upgrade options.



# Quantium 510

Our leading multiproduct dispenser with smart retractable hose management design. Choose from a complete suite of payment and upgrade options.





### Less service, less hassle

Tokheim's Quantium dispensers have been independently verified to have less service interventions than other industry installed and supplied pumps. Greater uptime means improved throughput and your customers can rely on your service station for a faster and more pleasant refuelling experience.





# TQM Drift Comparison over 12m litres O% Solution Litres (000 000') TOKHEIM Quantium Manufacturer B Old Generation Piston Meter

# Maximum accuracy, minimal drift

The TQM meter exhibits minimal drift performance over the lifetime of the dispenser, helping our customers to reduce fuel loss to a minimum. Its robust design ensures it is suitable to work in the harshest conditions with a wide variety of fuel types.



### **Quantium 410**

## Technical Specifications\*

### **Base models**

- Standard speed (40 l/min)
- · High speed (80 l/min)
- Very high speed (130 l/min)
- Satellite models
- Double-sided and single-sided models
- Combined standard speed-high speed
- Combined standard speed-very high speed
- Lifting slots solution for a safer installation
- Media Head with 17" VGA screen

Flow rates depend on model, underground site layout, site altitude, ambient temperature and selected options.

### **Optional features**

- Electronically Controlled Vapour Recovery (ECVR)
- Tokheim patented Self-Calibrating Vapour Recovery System – ECVR-SCS (including both monitoring and Self-Calibrating System)
- Several vapour recovery ground connections
- Automatic temperature compensation
- Electronic calibration
- Mains safety switch
- · Programming switch

- Single-phase motor
- Preset functions via push buttons or keypad
- Unit price display per product
- Product indication lights
- Speaker (one way sound)
- IR remote control compatible
- Ethernet Switch Connection
- SD Card for calculator data back-up
- Mechanical totalisers on meter
- Anti-magnetic electro-mechanical totalisers (single and double-sided)
- · Wide range of nozzles
- 40/80 l/min speed selection
- External filter pot for TQP-RS pump
- Several hydraulic inlet options
- Additional water filter
- Leak plate
- Wide range of stainless steel flexible connections to ease installation
- Submerged
- Ground frame
- Sightglass
- Satellite connection (single or double sided)
- E85 compliant
- Breakaway couplings
- · Low temperature kit

- Payment-integrated solutions for a wide range of markets
- · Narrow canopy
- Wafer stainless steel hydraulic top cover
- Various stainless steel cladding solutions
- Customised livery of complete dispenser
- Fire and tilt detection
- Media head with 17" VGA screen
- Fuel theft prevention

Only core features and options are listed. For more detailed information on available options, please contact your local Tokheim representative.

#### **Environmental conditions**

- Ambient temperature: -25°C to +55°C
- Cold climate: -40°C to +55°C (optional)
- Temperature of fluid: -25°C to +25°C
- Viscosity of fluid: < 10-4 m2/s
- Relative humidity: 5% to 95%
- Altitude: from sea level to 2,000 m

# Tokheim Worldwide



Corporate Headquarters Tokheim Group

Paris Nord 2 35, Allée des Impressionnistes Immeuble Le Cézanne 93420 Villepinte

Tel: +33 (0)1 49 90 77 00 Fax: +33 (0)1 49 90 77 77 For any further information and detailed contacts for each country, please visit our website at www.tokheim.com or email us at info@tokheim-international.com.

\*As Tokheim regularly improves its products in line with evolving market and regulatory requirements, it reserves the right to change any of the specifications of these products, and this document without prior notice.